


Id	Description	Material	Q.ty
1	DES FLAP Q CLICK	PP + GF	1
2	Gasket (not shown)	NBR	2

IP54	NEMA 12	ECOLAB	UL94-V0	ISO UV 4892-2A	RoHS COMPLIANT	PP+GF	+155 -40 °C	UL US APPROVED	UL TYPE 12	CE
------	---------	--------	---------	----------------	----------------	-------	----------------	----------------	------------	----

Flammability: UL94-V0, self-extinguishing
Temperature: -40°C ... +155°C
Properties: halogen-free, silicone-free

Recommended cut-out: 40 x 39 mm



Codice / Code		1731010408				Descrizione / Description		DES FLAP Q CLICK		Rev.	001
Materiale / Material	Colore / Color	Peso / Weight (g)		Unità di misura / Measure units	Formato / Format	Scala / Scale	UNI-ISO 2768-mK				
PP + GF	Black	-		mm	A4	1:2					
 www.detasultra.com				Data / Date	Numero foglio / Sheet number		Numero progetto / Project number				
				26/07/2023	-		-				
Disegn. / Drawn				Note / Notes							
Pozzi F.				-							

QUESTO DISEGNO E LE SUE INFORMAZIONI SONO STRETTAMENTE RISERVATE DI PROPRIETÀ DI DETAS SPA. NON UTILIZZARE PER SCOPI DIVERSI DA QUELLI PER CUI SONO STATE FORNITE. DO NOT SCALE DRAWING.