


Description	Material	Q.ty
1 DES PRED 32 Top	PP + GF	1
2 DES PRED 32 Bottom	PP + GF	1
3 DES PRED 32 gasket Top	TPE	1
4 DES PRED 32 gasket Bottom	TPE	1
5 M32 Locknut	PA	1
6 Nut (Black Dacromet finishing)	SS304	2
7 Screw Hex M5 L=38 (Black Dacromet finishing)	SS304	2

	<b>IP66</b>	<b>NEMA 12, 4X</b>	<b>UL TYPE 12, 4X</b>			<b>ECOLAB</b>			<b>RoHS COMPLIANT</b>	<b>IK10</b>	
--	-------------	--------------------	-----------------------	--	--	---------------	--	--	-----------------------	-------------	--

**Flammability:** UL94-V0, self-extinguishing  
**Temperature:** -40°C ... +155°C  
**Properties:** halogen-free, silicone-free

Recommended cut-out:  
 Ø 32.5 mm



Available ATEX version:  
 DES PRED 32 A - 1731350032

Codice / Code <b>1731050032</b>			Descrizione / Description <b>DESPRED 32</b>				Rev. 004
Materiale / Material see table	Colore / Color Black	Peso / Weight (g) 70.8	Unità di misura / Measure units mm	Formato / Format A4	Scala / Scale 1:1		
 <a href="http://www.detasultra.com">www.detasultra.com</a>			Data / Date 04/10/2021	Numero foglio / Sheet number -	Numero progetto / Project number -		
			Disegn. / Drawn ravezzano@detas.com	Note / Notes -			