


Id	Description	Material	Q.ty
1	DES PRED 63 Top	PP + GF	1
2	DES PRED 63 Bottom	PP + GF	1
3	DES PRED 63 gasket Top	TPE	1
4	DES PRED 63 gasket Bottom	TPE	1
5	M63 Locknut	PA	1
6	Nut (Black Dacromet finishing)	SS304	2
7	Screw Hex M5 L=60 (Black Dacromet finishing)	SS304	2

	IP66	NEMA 12, 4X	UL TYPE 12, 4X			ECOLAB			RoHS COMPLIANT	IK10	
--	-------------	--------------------	-----------------------	--	--	---------------	--	--	-----------------------	-------------	--

Flammability: UL94-V0, self-extinguishing
Temperature: -40°C ... +155°C
Properties: halogen-free, silicone-free

Recommended cut-out:
 Ø 63.5 mm



Available ATEX version:
 DES PRED 63 A - 1731350063

Codice / Code 1731050063			Descrizione / Description DESPRED 63				Rev. 004
Materiale / Material see table	Colore / Color Black	Peso / Weight (g) 130.8	Unità di misura / Measure units mm	Formato / Format A4	Scala / Scale 1:1		
 www.detasultra.com			Data / Date 04/10/2021	Numero foglio / Sheet number -	Numero progetto / Project number -		
			Disegn. / Drawn ravezzano@detas.com	Note / Notes -			