


Apertura consigliata:  
112 x 36 mm



	<b>IP66</b>	<b>NEMA 12, 4X</b>	<b>UL TYPE 12, 4X</b>	<b>HL3</b> EN 45545-2	<b>APPROVED</b> MARKET TYPE	<b>ECOLAB</b>	<b>UL94-V0</b>	<b>UV</b> ISO 4892-2A	<b>RoHS COMPLIANT</b>	
--	-------------	--------------------	-----------------------	--------------------------	--------------------------------	---------------	----------------	--------------------------	-----------------------	--

Id	Descrizione	Material	Q.t{
1	Des PDM 24-15	TPE+PA	1
2	Tappo	PE	4
3	Inserto M4	OTTONE	4

**Infiammabilità:** UL94-V0, autoestinguente  
**Temperatura:** -40°C ... +105°C  
**Proprietà:** senza alogeni, senza siliceni

Codice / Code <b>1732212415</b>		Descrizione / Description <b>DES PDM 24/15 FT</b>				Rev. 000
Materiale / Material See table	Colore / Color Grigio	Peso / Weight (g) -	Unità di misura / Measure units mm	Formato / Format A4	Scala / Scale 1:1	
 <b>DETASULTRA</b> <a href="http://www.detasultra.com">www.detasultra.com</a> <small>QUESTO DISEGNO E LE SUE INFORMAZIONI SONO STRETTAMENTE RISERVATE DI PROPRIETÀ DETAS SPA. NON UTILIZZARE PER SCOPI DIVERSI DA QUELLI PER CUI SONO STATE FORNITE. DO NOT SCALE DRAWING.</small>		Data / Date 04/10/2022	Numero foglio / Sheet number -	Numero progetto / Project number -		
Disegn. / Drawn Pozzi F.		Note / Notes -				