


| Id | Description | Material | Q.ty |
|----|----------------|----------|------|
| 1 | Body | TPE | 1 |
| 2 | Internal frame | PA | 1 |



Flammability: UL94-V0, self-extinguishing
Temperature: -40°C ... +105°C
Properties: halogen-free, silicone-free

Recommended cut-out:
112 x 36 mm

| | | | | | | | |
|---|----------------------|----------------|---------------------|---------------------------------|----------------------------------|---------------|------|
| Black color version: DES-PDM-24/42B: 1732013443 Threaded inserts version: DES-PDM-24/42G FT: 1732212442 ATEX grey version: DES-PDM-24A/42G: 1732312442 ATEX black version: DES-PDM-24A/42B: 1732313442 | Codice / Code | | | Descrizione / Description | | | Rev. |
| | 1732012442 | | | DES PDM 24/42 | | | 003 |
| | Materiale / Material | Colore / Color | Peso / Weight (g) | Unità di misura / Measure units | Formato / Format | Scala / Scale | |
| See table | Grey | - | mm | A4 | 1:1 | | |
| www.detasultra.com <small>QUESTO DISEGNO E LE SUE INFORMAZIONI SONO STRETTAMENTE RISERVATE DI PROPRIETÀ DETAS SPA. NON UTILIZZARE PER SCOPI DIVERSI DA QUELLI PER CUI SONO STATE FORNITE. DO NOT SCALE DRAWING.</small> | | | Data / Date | Numero foglio / Sheet number | Numero progetto / Project number | | |
| | | | 22/11/2021 | - | - | | |
| | | | Disegn. / Drawn | Note / Notes | | | |
| | | | ravezzano@detas.com | - | | | |