DES ATEX

Splittable frames for cables with and without connectors

The DES cable entry system consists of a splittable frame designed to accommodate small (SPP), multiple (X) or large (SPG) grommets for cables with and without connectors. The grommets can be freely positioned into the frame.
The overmolded gasket guarantees faster installation times and the complete V0 self-extinguishing feature of the system.
DES ATEX series can be used in zone 2 and 22.

Material: PP+GF, halogen-free, silicone-free
Flammability: self-extinguishing acc. UL94-V0
Temperature: -40°C... +50°C (static)

RELATED PRODUCTS

- SPP A (page 189)
- SPG A (page 190)
- SPP PA (page 200)
- SPG PA (page 201)
- HY360 hydraulic punch driver (page 179)
- PF cable entry system plates (page 181)

Model	Code	Dimensions (mm)	Max. cut-out (mm)	Pcs (/pack)
DES 24A	1731310024	146 x 61	112 x 36	
DES 16A	1731310016	120 x 61	86 x 36	
DES 10A	1731310010	99 x 61	65 x 36	
DES QA	1731310008	74 x 61	40 x 36	
DES L1A	1731310001	54,3 x 41	21 x 18	1
DES L2A	1731310002	74 x 41	40 x 18	
DES L3A	1731310003	99 x 41	63 x 18	
DES L4A	1731310004	120 x 41	86 x 18	
DES L5A	1731310005	146 x 41	112 x 18	
Upon request	1731991020	Set of 4 mounting screws in AISI304 with Black Geomet finishing		10

IP66 · NEMA 12, 4X · UL TYPE 12, 4X* *indoor only · HL3 EN 45545-2 · ECOLAB · UL94-V0 · UV ISO 4892-2A · RoHS COMPLIANT · IK10

© Detas SpA - ISO9001/ ISO14001 certified company
Via Treponti, 29 - 25086 Rezzato BS - Italy - Tel. +39 030 2594120
info@detasultra.com - **www.detasultra.com**