

## DESPRED ATEX



## Divisible cable gland with locknut

- Frame screws in AISI304 Stainless Steel with Black Dacromet finishing
- M25, M32 and M63 metric sizes
- ▶ IP66 and NEMA 4X\* certified
- Strain relief according to EN 62444
- Sturdy construction IK10
- Integrated gasket







The DESPRED series are divisible cable glands for metric threads.

The 63 model can be used with small, multiple and large grommets for cables up to 34 mm diameter. With multiple grommets it is possible to accommodate up to 16 cables. Future cable size changes can also be easily accommodated using various grommets.

DESPRED ATEX series can be used in zone 2 and 22 according to IEC 60079-10.

## Technical data

Material: PP+GF Flammability: self-extinguishing acc. to UL94-V0 Temperature: -40°C... +155°C (static) Features: halogens and silicones free

## **Related products**


RoHS


IK10

SPP grommets (from page 43) SPG grommets (from page 49) HY360 hydraulic punch driver (page 129) Divisible locknuts (page 37-38)

	Model	Code	Some possible configurations	Cut-out Ø [mm]	Pcs /pack	
	DESPRED 25A	1731350025		25,5		
	DESPRED 32A	1731350032		32,5	10	
	DESPRED 63A	1731350063		63,5		

Dimensions [mm]






NEMA


12, 4X<sup>\*</sup>

**UL** TYPE

12, 4X







EN 45545-2

\* Indoor only

c **Ru**s



**IP66** 

© Detas SpA - ISO9001/ ISO14001 certified company

Via Treponti, 29 - 25086 Rezzato BS - Italy - Tel. + 39 030 2594120 - info@detasultra.com - www.detasultra.com

ECOLAB

UL94-V0