





DES grommets - large - for cables without connectors - double membrane

- ▶ K1, K2 e K3 for sigle cables with diameters from 16 to 30 mm
- ► K0 blind grommet

Mardal

▶ IP66 for SPG K1, K2 and K3





The SPG K are blind grommets which can be also used for cables without connectors with diameter from 16 to 30mm.

The SPG K0 can be perforated but the IP protection is not guaranteed.

Thanks to the double membrane in the SPG K1-K2-K3 grommets an optimal dust and water protection are achieved.

SPG K ATEX series can be used in zone 2 and 22 according to IEC 60079-10.

Technical data

Material: TPE

Flammability: self-extinguishing acc. to UL94-V0 (grey or black) Temperature: -40°C... +110°C (static) Features: halogens and silicones free

Related products

RoHS

ϓυν

UL94-V0

(Ex)

DES 24	DESPRED	DES 16M
DES 16	DESCLICK	DES 16MX
DES 10	DES 24M	
DES Q	DES 24MX	


Model	Code	Ø Cable	Model	Code	Pcs
		[mm]			/pack
SPG KOGA	1731322300	max. 32	SPG KOBA	1731322400	
SPG K1GA	1731322310	16-22	SPG K1BA	1731322410	10
SPG K2GA	1731322320	23 - 26	SPG K2BA	1731322420	10
SPG K3GA	1731322330	26 - 30	SPG K3BA	1731322430	




NEMA

12, 4X[°]

Dimensions [mm]



IP66



* Indoor only



c SU'us

© Detas SpA - ISO9001/ ISO14001 certified company

EN 45545-2

2

Via Treponti, 29 - 25086 Rezzato BS - Italy - Tel. + 39 030 2594120 - info@detasultra.com - www.detasultra.com

ECOLAB