



DES FT



Splittable frame with threaded inserts

FEATURES

- Flat surface without dirt deposit
- **Rear installation with M4 threaded inserts**
- IP66 and NEMA 4X* certified with all configurations of grommets
- Strain relief according to EN 62444
- Sturdy construction IK10
- Overmolded gasket acc. to UL94-V0

The DES FT splittable frames are equipped with threaded inserts and with front taps which allow the installation on the rear part of the panel and keep the front part clean avoiding dirt accumulation.

All the other technical data of the DES FT frames are exactly the same of DES Series.

Material: PP+GF, halogens and silicones free

Flammability: self-extinguishing acc. to UL94-V0

Temperature: -40°C... +155°C (static)

RELATED PRODUCTS

- SPP grommets (from page 46)
- SPG grommets (from page 52)
- DES Cover (page 26)
- DES Flap (page 27)
- HY360 hydraulic punch driver (page 139)
- PF/PFX cable entry system plates (from page 140)
- DES caps (page 61)



M4 threaded inserts



	Model	Code	Some possible configurations	Max. cut-out (mm)	Pcs (/pack)
NEW	DES L1 FT	1731410001		21 x 18	10
	DES L2 FT	1731410002		40 x 18	
	DES L3 FT	1731410003		63 x 18	
	DES L4 FT	1731410004		86 x 18	
	DES L5 FT	1731410005		112 x 18	
	DES Q FT	1731410008		40 x 39	
	DES 10 FT	1731410010		63 x 39	
	DES 16 FT	1731410016		86 x 39	
	DES 24 FT	1731410024		112 x 39	

* Indoor only



IP66

NEMA 12, 4X*

UL TYPE 12, 4X



ECOLAB



IK10

