



# DES Q



## Splittable frame for cables with and without connectors

### FEATURES

- For 4 small grommets or 1 big grommet
- Frame screws in AISI304 Stainless Steel
- IP66 and NEMA 4X\* certified with all configurations of grommets
- Strain relief according to EN 62444
- Sturdy construction IK10
- Overmolded gasket acc. to UL94-V0
- ATEX version on request (Group 7)
- Threaded inserts version on request
- Max 16 cables



The DES Q cable entry system consists of a splittable frame designed to accommodate small (SPP), multiple (X) or large (SPG) grommets for cables with and without connectors.

With all combinations of grommets, single, double, quadruple, big, the IP66 and NEMA 4X\* are guaranteed.

The overmolded gasket guarantees faster installation times and the complete V0 self-extinguishing of the system.

**Material:** PP+GF, halogens and silicones free

**Flammability:** self-extinguishing acc. to UL94-V0

**Temperature:** -40°C... +155°C (static)

| Model        | Code       | Some possible configurations                                    | Cut-out (mm) | Pcs (/pack) |
|--------------|------------|---|--------------|-------------|
| DES Q        | 1731010008 |   | 40 x 36      | 10          |
| Upon request | 1731991020 | Set of 4 mounting screws in AISI304 with Black Geomet finishing |              |             |



### RELATED PRODUCTS

- SPP grommets (from page 46)
- SPG grommets (from page 52)
- DES Cover (page 26)
- DES Flap (page 27)
- HY360 hydraulic punch driver (page 139)
- PF/PFX cable entry system plates (from page 140)
- DES caps (page 61)
- Intumescent gasket (page 127)



\* Indoor only

### Dimensions (mm)



IP66

NEMA 12, 4X\*

UL TYPE 12, 4X



ECOLAB

UL94-V0



RoHS COMPLIANT

IK10

