



OSF90



Divisible cable glands with 90° entry

FEATURES


- 90° cable entry system
- Without screws
- IP54
- Locknut included
- Available colors: grey and black

OSF90 is a 90° divisible cable gland with metric thread especially designed for cables with connectors. The 90° entry systems protects the cables from frontal damage and provides an elegant design. OSF 90 can be equipped with SPC grommets with single or multiple holes for both black and grey UL94V0 colors.

Material: PC, halogens and silicones free
Flammability: self-extinguishing acc. to UL94-V0
Temperature: -40°C... +130°C (static)

RELATED PRODUCTS


- SPC grommets (from page 53)
- Divisible locknuts (page 50)
- HY360 hydraulic punch driver (page 174)



Model	Code	Max. allowable grommet			Max. cut-out (Ø mm)	Pcs (/pack)
		□ ●	□ ● ●	□ ● ● ●		
OSF90 16G	1731052916	SPC 10	SPC 2x4	SPC 4x4	16,5	10
OSF90 20G	1731052920	SPC 13	SPC 2x5	SPC 4x5	20,5	
OSF90 25G	1731052925	SPC 13	SPC 2x7	SPC 4x6	25,5	
OSF90 32G	1731052932	SPC 13	SPC 2x7	SPC 4x6	32,5	
OSF90 16B	1731052917	SPC 10	SPC 2x4	SPC 4x4	16,5	
OSF90 20B	1731052921	SPC 13	SPC 2x5	SPC 4x5	20,5	
OSF90 25B	1731052926	SPC 13	SPC 2x7	SPC 4x6	25,5	
OSF90 32B	1731052933	SPC 13	SPC 2x7	SPC 4x6	32,5	

Dimensions (mm)

Cable bend radius
max. 10 mm



IP54

NEMA 12



IK10