

DES 16M



Splittable frame for cables with and without connectors

- Multiple configurations with small and big grommets
- Frame screws in AISI304 Stainless Steel
- External gasket included
- ▶ Strain relief according to EN 62444
- Sturdy construction IK10
- Threaded inserts version on request








| Model | Code | Some possible configurations | Max. cut-out [mm] | Pcs /pack |
|------------------|------------|--|----------------------|---------------------|
| DES 16M | 1731010216 | | 86 x 40 | 10 |
| | | | | |
| Upon request: | 1731991020 | Set of 4 mounting screws in AISI304 with Black Dacromet finishing | | 10 |

Dimensions [mm]



cables with or without connector or one or two cables up to 35mm diameter to pass through electric cabinet or machines walls. The small and big grommets can be freely

The DES 16M splittable frame allow up to 32

positioned inside the frame. The DES 16M frame is the base structure for the expandable MX version.

Technical data

Material: PP+GF

Flammability: self-extinguishing acc. to UL94-V0

Temperature: -40°C... +155°C (static) **Features:** halogens and silicones free

Related products

SPG grommets (from page 38) SPP grommets (from page 31) DES Cover HY360 hydraulic punch driver

CRUS IP54 12 ECOLAB UL94-VO



© Detas SpA - ISO9001/ ISO14001 certified company Via Treponti, 29 - 25086 Rezzato BS - Italy - Tel. +39 030 2594120 - info@detasultra.com - www.detasultra.com

⊕

Э

32 63